

750 Watt Ku-Band High Efficiency Antenna Mount High Power Amplifier

Green Power
by XICOM TECHNOLOGY



FEATURES

- *13.75 to 14.5 GHz*
- *Compact size and weight*
- *300 watts linear power*
- *Operates to +60°C*
- *Optional linearizer*
- *High efficiency peak TWT*
- *Ethernet interface*

The **XTD-750KHE** is a highly compact, rugged antenna mountable power amplifier designed for high efficiency and long life. The **XTD-750KHE** design uses high efficiency, dual-stage collector peak Traveling Wave Tubes (TWT) to fit a 750 watt rated amplifier into the package size previously offered as a 400 watt TWTA. Some benefits of this type of tube are: significantly reduced prime power consumption, lower internal operating temperatures, and reliability enhancement.

RF filters, cooling, and monitoring & control (M&C) systems are all self-contained within the High Power Amplifier (HPA). An ethernet M&C interface is included.


The **XTD-750KHE** may be configured for single thread, redundant, or phase-combined operation.




PERFORMANCE SPECIFICATION

Parameters	XTD-750KHE	XTD-750KHE1
FREQUENCY RANGE	13.75 to 14.5 GHz	12.75 to 14.5 GHz
OUTPUT POWER		
Peak TWT Power	750 Watts (58.7 dBm)	
Maximum CW power (P _{MAX})	355 Watts (55.5 dBm)	
Linear Power (P _{LINEAR})	300 Watts with optional linearizer (54.8 dBm) 165 Watts without linearizer (52.2 dBm)	
GAIN		
Large Signal (minimum)	70 dB	
Small Signal (minimum)	70 dB	
Attenuator Range (continuous)	30 dB, 0.1 dB steps	
Maximum SSG Variation Over		
Any Narrow Band	1.0 dB per 80 MHz	
Full Band	2.5 dB per 500 MHz	
Slope (maximum)	± 0.02 dB/MHz	
Stability, 24 hr. (maximum)	± 0.25 dB	
Stability, Temperature (maximum)	± 1.0 dB over temperature range at any frequency	
INTERMODULATION (maximum) relative one of two equal carriers	-25 dBc @ P _{LINEAR}	
SPECTRAL REGROWTH @ 1 SR offset	-30 dBc @ P _{LINEAR}	
AM/PM CONVERSION (maximum)	2.0 deg/dB @ P _{LINEAR}	
HARMONIC OUTPUT (maximum)	-60 dBc	
NOISE POWER (maximum)		
Transmit Band	-70 dBW/4 kHz	
Receive Band	-150 dBW/4 kHz 10.95 to 12.75 GHz	-150 dBW/4 kHz 10.95 to 11.75 GHz
GROUP DELAY (maximum)		
Bandwidth	Any 80 MHz	
Linear	0.01 nS/MHz	
Parabolic	0.005 nS/MHz ²	
Ripple	0.05 nS/Pk-Pk	
RESIDUAL AM NOISE (maximum)	-50 dBc to 10 kHz -20 (1.5 + logf) dBc 10 to 500 kHz -85 dBc above 500 kHz	
PHASE NOISE (maximum)	12 dB below IESS phase noise profile AC fundamental -50 dBc Sum of all spurs -47 dBc	
VSWR		
Input (maximum)	1.3:1	
Output (maximum)	1.3:1	

BLOCK DIAGRAM



OUTLINE DRAWING



PRIME POWER

100 to 240 VAC
47 to 63 Hz, Single Phase
1450 VA Typical @ P_{LINEAR} 180 to 240 VAC
1650 VA Typical @ P_{LINEAR} 100 VAC
0.95 Minimum Prime Power Factor



ENVIRONMENT

NONOPERATING TEMPERATURE RANGE	-50°C to +70°C
OPERATING TEMPERATURE RANGE	-40°C to +60°C (2°C/1000 Feet Derating)
HUMIDITY	Up to 100% Condensing
ALTITUDE	10,000 Feet MSL Max.
SHOCK AND VIBRATION	Normal Transportation
COOLING	Forced Air

INTERFACE

Type	Function	
LOCAL CONTROL	Prime Power ON/OFF	Local/Remote
	Power Supply ON/OFF	HV ON/OFF
LOCAL STATUS	Tri-Color LED:	
	Fault: Red	Standby: Continuous Amber
	HV ON: Green	FTD: Flashing Amber
REMOTE CONTROL	HV ON/OFF	Constant Power
	Min/Max Power Alarm/Fault	Gain
	Reflected Power Alarm/Fault	Fault Reset
	Heater Standby ON/OFF	Units (Watts, dBm, dBW)
REMOTE STATUS	Power Out	Reflected Power
	Helix Current	Helix Voltage
	Heater Hours	Beam Hours
	Attenuator Setting	Units Selection
	TWT Temperature	Faults:
		High VSWR High Voltage Helix Current TWT Temperature 10 MHz Lock
FORM C DRY CONTACT CLOSURE	Summary Fault	
COMPUTER PORT	Hardware Interface: RS-232 & RS-422/485 Ethernet	Xicom Command Set: ASCII Commands
RF MONITOR PORT	-43 dB Coupling Value (nominal.)	

OPTIONS

- Remote External Controller
- 1:1, 1:2, 1:N Redundancy
- Linearizer
- Alternate Frequencies Available

Headquarters

Comtech Xicom Technology, Inc.
3550 Bassett Street
Santa Clara, CA 95054
USA

Phone: +1-408-213-3000

Fax: +1-408-213-3001

email: sales@xicomtech.com

Web: www.xicomtech.com

Europe Sales Office

Comtech Xicom Technology Europe, LTD
4 Portland Business Center
Manor House Lane
Datchet
Berkshire SL3 9EG
United Kingdom

Phone: +011 44 (0) 1753 549 999

Fax: +011 44 (0) 1753 549 997

email: sales@xicomeurope.com

Web: www.xicomtech.com

Asia Sales Office

Comtech Xicom Technology
150 Cecil Street
#08-02
Singapore 069543

Phone: +011 65 6325 1953

Fax: +011 65 6325 1950

email: asiasales@xicomtech.com

Web: www.xicomtech.com

